



TLS-XB for TLS4

Proven Wet Stock Management

Combine **TLS-XB** expansion box with your **TLS4** to provide a flexible system solution that grows with your fuel site.

FEATURES

TLS-XB expands your total inputs from 12 to 76

BENEFITS

- Compatible with existing modules (see table)
- Each **TLS-XB** can accommodate 4 modules
- Provides additional Input and Output Relay capabilities

SPECIFICATIONS

Description:

TLS-XB (Expansion Box)

Temperature Rating

Storage:

-40° C to + 70° C

-40° F to + 158° F

Operating:

0° C to + 40° C

32° F to + 109° F

Console Compatibility:

TLS4

Dimensions:

11in. H x 8 in. W x 5 in. D



TLS-XB Compatible Device Table

Device Name	Module Type	Module Part Number	Total # Inputs Per Module	Total Devices Per System
DPLLD	Universal Sensor Module (USM)	332812-001	16	64
Probes				
Sensors				
Mechanical Pulser	Mechanical Dispenser Interface Module (MDIM)	330020-681	12	48
Low Voltage Pulser	Low Voltage Dispenser Interface Module (LVDIM)	330020-680	12	48
Input/Output	Input /Output Interface Module (UIOM)	332813-001	5 Dry Contact Relays 5 High Voltage Inputs 4 External Dry Contacts	Dry Contacts Relays (<=240 Vac) High Voltage Inputs (<=240 Vac) External Dry Contacts (<=12Vdc)
	10 Amp Controller Module	333564-001	6 High Voltage Inputs 6 Dry Contact Relays	6 High Voltage Inputs 6 Dry Contact Relays ¹

¹ 10 Amp Relay must be installed in slot 4 of TLS-XB



Ordering Information

Part #	Description
860390-100	TLS-XB Expansion Box
333416-05	3 ft. Cable to Connect TLS-XB to TLS4
333411-016	16-input iButton for TLS-XB connected to TLS4
333411-032	32-input iButton for TLS-XB connected to TLS4
333411-048	48-input iButton for TLS-XB connected to TLS4
333411-064	64-input iButton for TLS-XB connected to TLS4

The **TLS-XB** requires an expansion cable assembly for proper connection to the system.