



## VAPT.E37780 Solenoids for Use in Hazardous Locations

[Page Bottom](#)

### Solenoids for Use in Hazardous Locations

[See General Information for Solenoids for Use in Hazardous Locations](#)**PETER PAUL ELECTRONICS CO INC**

E37780

480 John Downey Dr  
PO BOX 1180  
New Britain, CT 06051-2910 USA

**Class I, Groups A, B, C and D; Class II, Groups E, F and G.**

Model Nos. OELW51, -52, -53, OEW-51, -52, -53, -54, -55, -56, followed by three suffix letters, followed by D, U, V, X or Z, followed by C or CC. Model No. may be preceded by V or VO.

Model Nos. OELW51, -52, -53, OEW-51, -52, -53, -54, -55, -56, followed by Z, followed by any four digit number, followed by a suffix letter, followed by C or CC, followed by A, P or S. Model No. may be preceded by V or VO.

**Class I, Groups C and D; Class I, Div. 2, Groups A, B, C and D; Class II, Groups E, F and G.** Model Nos. OE21-26 incl., OEH22 followed by Z, followed by additional suffix letters or letters with a number, followed by a single letter, followed by BC, BCC, C, CC E or EC, followed by F, H, M or P. Solenoids with suffix P may be marked "Rain tight".

Model Nos. OE51-56 incl. followed by Z, followed by additional suffix letters or letters with a number, followed by a single letter, followed by C, CC E or EC, followed by B, F, H, M or P. Solenoids with suffix P may be marked "Rain tight" . Model No. may be preceded by V or VO.

Model Nos. OEL51, -52, -53 followed by Z, followed by any 4 digit number, followed by a single letter, may be followed by B, C, CC, E, EC, F, H, M, P or S. Solenoids with suffix P may be marked "Rain tight" or Type 4x. Model number may be preceded by a V or VO.

Model Nos. OELL51, -52, -53 followed by Z, followed by any 4 digit number, may be followed by B, C, CC, M or P. Model number may be preceded by a V or VO.

Model Nos. OE21-26 incl., OEH22 followed by additional suffix letters or letters with a number, followed by D, U, X, Z, followed by B, C, CC E or EC, followed by A, F, H, M, P or S, followed by additional numbers. Solenoids with suffix P may be marked "Rain tight".

Model Nos. OE51-56 incl. followed by additional suffix letters or letters with a number, followed by D, U, V, X or Z, followed by B, C, CC, E or EC, followed by A, B, D, F, H, M, P or S, followed by additional numbers. Solenoids with suffix P may be marked "Rain tight" .

Model Nos. OEL51, -52, -53 followed by additional suffix letters or letters with a number, followed by D, U, V, X or Z, followed by B, C, CC E or EC, followed by A, B, F, H, M, P or S, followed by additional numbers. Solenoids with suffix P may be marked "Rain tight" or Type 4x. Model No. may be preceded by V or VO.

Model Nos. OELL52, -53 followed by additional suffix letters or letters with a number, followed by D, U, V, X or Z, followed by B, C, E or EC, followed by B, F, H, M, P or V, followed by additional numbers. Solenoids with suffix P may be marked "Rain tight" or Type 4x.

**Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Groups F and G Hazardous Locations.** Models ON71 to ON76, inclusive; followed by J, K, N, O, P, R, T; followed by J, K, N, O, P, R; followed by letter D; followed by D or Z; followed by B, BC, C or CC; followed by A, F, P or S.

Models ON71 to 76, inclusive; followed by Z0000 to Z9999, inclusive; followed by Letter A, C, D, E, F, G, H, J, K, L, N, O, P, R, S, T, U, V, W, X, Y or Z; followed by B, BC, C or CC; with or without A, F, P or S.

[Last Updated](#) on 2016-01-25[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".